

Certified Environmental Radon Services

PO Box 727, Farmingdale, NJ 07727 (732) 534-4892 Laboratory #13035 NJDEP MEB #94012 NRPP Charcoal Canister AC-8303

RADON TEST INFORMATION FORM

FAILURE TO COMPLETE ALL FIELDS MAY DELAY OR PROHIBIT ANALYSIS

TESTING LOCATION					
ADDRESS:					
	STREET				
CITY	MUNICIPALITY	COUNTY	STATE	ZIP	
OWNER ADDRESS IF DIFFERENT FROM ABOVE:					
ADDRESS.					
STREE	ET	CITY	STATE	ZIP	
FLOOR LEVEL TESTED:	Basement / First Floor / Seco	ond Floor / Other:			
BUILDING TYPE: (Circle One) R=residential	cle One) Non-R / Non-R/Child Care Center / School (Must include NJDOE School code below)				
TEST PURPOSE: (Circle One)	Real Estate / Screening / Post Mitigation				
FOUNDATION TYPE: Basement / Crawlspace / Slab on Grade / Combination (Circle all that Apply)					
Closed house condition	ns? YES NO				
CRM Model:	CRM Device Number:	CRM Calibr	r. Exp. Date:	(m/d/y)	
Deploy License #	Retrieval License #_	En	nail Results To:		
Deploy Tech	Retrieval Tech	M	1ail to:		
CANISTER ID#:	DUPLICATE ID#	BL/	ANK ID #:		
START DATE:		TOP DATE:			
Month / I START TIME:	Day / Year AM / PM S	Month / D TOP TIME:	ay / Year	AM / PM	
XSignature of Owner to Release this test to the following: By Signing Above the Owner Waives Their Right to Confidentiality					
	THIS BOX	FOR LAB USE ONLY			
Date:	Result: / / pCi/l	L Initial	WEIGHT		
<u> </u>	incount	Final			
Lab Tech:					



These instructions are for anybody placing a radon canister.

CLOSED HOUSE CONDITIONS

The house should be under "Closed House" conditions for at a minimum of 12 hours prior to and for the duration the Radon test is exposed. This data sheet is for residences.

Choice of Location

To screen the residence for Radon exposure, select the lowest livable level of the building. This is usually the basement. Avoid bathrooms, kitchens, laundry rooms, closets, garages, and attics. Stay away from direct sun light, forced air registers, radiators, vents, doors, windows, fire-places, and basement sump pits. Place the canister a mini-mum of 3 feet from walls with openings to the outside, 1 foot below the ceiling, 4 inches from other objects, and 20 inches above the ground.

Instructions

- 1) Remove the plastic tape from the side of the canister. Open the canister by removing the metal lid and **SAVE THE LID AND TAPE** for resealing at the end of the test after the exposure is completed. Place the canister open face upon the testing site. (See "Choice of Location" for a guide on correct test placement) Enter the "Opened" date and time in the space provided on reverse side.
- 2) When the exposure is finished in 2-6 days, replace the metal lid on the canister and seal its perimeter where the seams meet using the tape provided. Enter the "Closed" date and time in the space provided on reverse side.
- 3) Immediately return sealed canister to:

Certified Environmental Radon Services PO BOX 727, Farmingdale, NJ 07727

The canister must be exposed for 2-6 days. It is very important to observe these limits and return the canister to us within 7 days after exposure is completed and the canister is closed.

Test results will not be issued unless data sheets are completely filled out. Missing data that would affect the test result will make the test INVALID.

RADON TESTING IN PROGRESS DO NOT TOUCH